



JM Ceiling Pro Lucent

JM Ceiling Pro Lucent



PVC-free



tear-resistant



textile appearance



translucent



water resistant



good crease recovery



easy to clean



flame retardant

JM Ceiling Pro Lucent

digitally printed with latex ink





JM Ceiling Pro Lucent FR				
Article		03-2113-3100	03-2113-4100	03-2113-5100
Basic material		100 % polyester (polymer coated)		
Weave	woven fabric			
Width		310 cm / 122"	410 cm / 161"	510 cm / 201"
Weight approx.	EN ISO 2286-2	210 g/m² / 6,2 oz/yd²		
Thickness approx.	EN ISO 2286-3	0,38 mm / 0,015"		
Light fastness	EN ISO 105-B02	7		
Dimensional change (temperature)	110°C, 2 min	warp: ≤ 0,5 % weft: ≤ 0,5 %		
Dimensional change (moisture)	DIN 53892-2	warp: ≤ 0,5 % weft: ≤ 0,5 %		
Tensile strength	EN ISO 1421	warp: ≥ 800 N / 5 cm weft: ≥ 500 N / 5 cm		
Tear strength	EN ISO 1875-3	warp: ≥ 30 N weft: ≥ 40 N		
Fire classification	EN 13501-1	B-s1, d0		
Light transmittance	EN 410	approx. 30 %		
Degree of whiteness approx.	according to Berger	approx. 80		
Printability		yes (UV, latex, solvent)		
Care instruction	spongeable			
Manufacturing guidance		to cut with cold knife		
Roll length approx.	50 m / 55 yd			

The information provided in this document do not exempt processors from carrying out own tests and trials as further handling and processing may show significant effects on our products. Application, utilization and processing of products are beyond our control and are therefore the sole responsibility of the processors.

All specifications are based on average values and may deviate within the standard tolerance limits. Subject to technical modifications.

Product certificates and guarantees



REACH
compliant

low
VOC



Sustainable building certificates

All JM fabrics certified according to SCS Advantage™ Gold can contribute to credits in sustainable building certifications, such as DGNB, BREEAM and LEED.

